

## Billi Spring 350 Bottling System Specification Sheet



Instant chilled & sparkling filtered water.

**Practical, reliable and visually striking, this innovative tap brings a high capacity refreshment solution to any commercial space.**

**Adjustable sparkling water**

Adjust the level of sparkling to suit your taste with adjustable controls up to 5 bar of CO<sub>2</sub> pressure.

**Adjustable chilled temperature**

Fixed electronic controlled to optimum temperature.

**Higher dispense height**

Will fill even narrow neck bottles up to 310mm high. Fast and efficient.

**Higher volume**

Up to 60 litres of chilled or sparkling water dispensed per hour. Ideal for board rooms, meeting rooms, receptions and other areas of high volume chilled and sparkling requirement. The system is adjustable for taste which gives the equivalent of 250-350 glasses of water per 1.1kg cylinder. Packaging to include CO<sub>2</sub> canister.

**POWER:** 1 x single 13amp power socket

**WATER:** potable main water supply terminated with valve

**DRAINAGE:** drainage connection for drainage front drip tray connection

**VENTILATION:** Unit requires ventilation. For more information please download our [Ventilation Guidance](#).

### Specifications and guide to standard model selection

Product Number	Description	Suggested no. of persons	Chilled & sparkling litres/ hour	Boiling cups / hour	Power required (amps)	Unit Height (mm)	Unit Width (mm)	Unit Depth (mm)
829000UK	Billi Spring 350 Bottling System	350	60	n/a	1 x13	550	245	320

As Billi UK Limited has a policy of continual improvement, all details are subject to change without notice. All goods are sold subject to our published terms and conditions.